

http://m.egovframe.go.kr/mguide3.5/guide/components/progress/progress.do;jsessionid=ldJHmT6h1AZ5j5fd3pggKzbYcqmO2FBvZlvkHriOtgKaBbN8OqiOD9cUly2F0RRY.was2_servlet_engine3

Loader Widget

Loader Widget provides loading dialog output for content switching via Ajax

Basic Code

Loader Widget can be applied if related properties of `$.mobile.loader.prototype.options` is added to pageinit event.

- `$(document).on("pageinit", function() {`
- `$.mobile.loader.prototype.options.text = "loading";`
- `$.mobile.loader.prototype.options.textVisible = false;`
- `$.mobile.loader.prototype.options.theme = "a";`
- `$.mobile.loader.prototype.options.html = "";`
- `});`

Also, configuration by using `$.mobile.loading` is available.

- `$.mobile.loading("show", {`
- `text: "foo",`
- `textVisible: true,`
- `theme: "z",`
- `html: ""`
- `});`

Option

html

Used for replacing internal HTML if value is not empty

- `$(".selector").loading({ html: "<imgsrc='jquery-logo.png' /><h2>is loading for you ...</h2>" });`

text

Set text value for loading message

- `$(".selector").loading({ text: "Loading Page..." });`

textVisible

Text value is used if value is set as true

- `$(".selector").loading({ textVisible: true });`

textonly

Image is not shown and only text message is used if value is set as true

- `$(".selector").loading({ textonly: true });`

theme

Set color theme for Loader Widget

- `$(".selector").loading({ theme: "b" });`

Methods

checkLoaderPosition()

Confirm that the location of the loader is fixed in the center

- `$(".selector").loading("checkLoaderPosition");`

fakeFixLoader()

For browsers that do not support fixed loader, fix location of the loader in the center

- `$(".selector").loading({ text: "Loading Page..." });`

hide()

Hider Loader Widget

- `$(".selector").loading("hide");`

hidePageLoadingMsg()

Hide Loader message configured via `$.mobile.showPageLoadingMsg()`.

deprecated in version 1.2 and deleted in version 1.4.

replace as `$.mobile.loading('hide')`.

loading()

Display or hide Loader message set via `$.mobile.loader`

- `$(".selector").loading("loading");`

`resetHtml()`

Initiallize HTML configuration

- `$(".selector").loading("resetHtml");`

`show()`

Print Loader

- `$(".selector").loading("show");`

`showPageLoadingMsg()`

Print page loading message

deprecated in version 1.2 and deleted in version 1.4.

replace as `$.mobile.loading('show')`.

- `$.mobile.loading('show', { theme: "b", text: "This is only a test", textonly: true });`

Events

`create(event, ui)`

Event triggered when loader widget is created

Example

- `<div data-role="page" id="page1">`
 - `<div data-role="content">`
 - `<div data-role="controlgroup">`
 - `<button class="show-page-loading-msg" data-theme="a" data-textonly="false" data-textvisible="false" data-msgtext="" data-icon="arrow-r" data-iconpos="right"p">Default loader</button>`
 - `<button class="show-page-loading-msg" data-theme="a" data-textonly="true" data-textvisible="true" data-msgtext="Text only loader" data-icon="arrow-r" data-iconpos="right">Text only</button>`
 - `<button class="show-page-loading-msg" data-theme="a" data-textonly="false" data-textvisible="true" data-msgtext="Loading theme a" data-icon="arrow-r" data-iconpos="right">Theme a</button>`
 - `<button class="show-page-loading-msg" data-theme="b" data-textonly="false" data-textvisible="true" data-msgtext="Loading theme b" data-icon="arrow-r" data-iconpos="right">Theme b</button>`
 - `<button class="show-page-loading-msg" data-theme="c" data-textonly="false" data-textvisible="true" data-msgtext="Loading theme c" data-icon="arrow-r" data-iconpos="right">Theme c</button>`
 - `<button class="show-page-loading-msg" data-theme="d" data-textonly="false" data-textvisible="true"`

- data-msgtext="Loading theme d" data-icon="arrow-r" data-iconpos="right">Theme d</button>
- <button class="show-page-loading-msg" data-theme="e" data-textonly="false" data-textvisible="true"
- data-msgtext="Loading theme e" data-icon="arrow-r" data-iconpos="right">Theme e</button>
- <button class="show-page-loading-msg" data-theme="a" data-textonly="true" data-textvisible="true"
- data-msgtext="Custom Loader" data-icon="arrow-r" data-html="
- <imgsrc='../_assets/images/jquery-logo.png' /><h2>is loading for you ...</h2>"
- data-iconpos="right"ble="false" data-msgtext="" data-icon="arrow-r" data-iconpos="right"p">Custom

HTML</button>

- <button class="hide-page-loading-msg" data-icon="delete" data-iconpos="right">Hide</button>

- <script>
- \$(document).on("click", ".show-page-loading-msg", function() {
 - var \$this = \$(this),
 - theme = \$this.jqmData("theme") || \$.mobile.loader.prototype.options.theme,
 - msgText = \$this.jqmData("msgtext") || \$.mobile.loader.prototype.options.text,
 - textVisible = \$this.jqmData("textvisible") || \$.mobile.loader.prototype.options.textVisible,
 - textonly = !\$this.jqmData("textonly");
 - html = \$this.jqmData("html") || "";
- \$.mobile.loading('show', {
 - text: msgText,
 - textVisible: textVisible,
 - theme: theme,
 - textonly: textonly,
 - html: html
- });
- })
- .on("click", ".hide-page-loading-msg", function() {
 - \$.mobile.loading("hide");
- });
- </script>