

## Footer bar

Footer bar is located at the bottom of the browser and can have components such as buttons, tabs, links, etc.

### Base Code

Footer bar is in black by default. The height of the Footer bar varies depending on the title size.

### Footer title

```
<div data-role="footer">
  <h1>Footer title</h1>
</div>
```

### Color Change

Add **data-theme='[applied theme: a~g]'** to base code `<data-role="footer">` tag. For color types, refer to [Header bar's color change](#).

### data-theme="b"

```
<div data-role="footer" data-theme="b">
  <h1>data-theme="b"</h1>
</div>
```

### Add Buttons

Adding an anchor link to Footer bar will create a button automatically. Multiple buttons can be created and automatically aligned to the right. For button shapes, refer to [UX Component ICon](#).

[Remove](#) [Add](#) [Up](#) [Down](#)

```
<div data-role="footer">
  <a href="index.html" data-role="button" data-icon="delete">Remove</a>
  <a href="index.html" data-role="button" data-icon="plus">Add</a>
  <a href="index.html" data-role="button" data-icon="arrow-u">Up</a>
  <a href="index.html" data-role="button" data-icon="arrow-d">Down</a>
</div>
```

---

### Button Alignment

To group buttons in the Footer bar, enclose buttons with `<div data-role="controlgroup" data-type="horizontal">`.

[Remove](#) [Add](#) [Up](#) [Down](#)

```
<div data-role="footer">
  <div data-role="controlgroup" data-type="horizontal">
```

```

    <a href="index.html" data-role="button" data-icon="delete">Remove</a>
    <a href="index.html" data-role="button" data-icon="plus">Add</a>
    <a href="index.html" data-role="button" data-icon="arrow-u">Up</a>
    <a href="index.html" data-role="button" data-icon="arrow-d">Down</a>
  </div>
</div>

```

## Add Components

In the Footer bar, you can add UX components to make it easier to transit pages and make adjustments.

## Tab Components

You can place [Tab components](#) in the Footer bar to make it easier to navigation between pages. [Footer Tab sample](#)

```

<div data-role="footer" data-theme="z" data-position="fixed">
  <div data-role="navbar">
    <ul>
      <li><a href="exHome.jsp">Home</a></li>
      <li><a href="header.jsp">Header bar </a></li>
      <li><a href="footer.jsp">Footer bar</a></li>
    </ul>
  </div>
</div>

```

## Other Components

You can place other components in the Footer bar.

Please select:

apple

```

<div data-role="footer" class="ui-bar" data-position="inline">
  <label for="select-choice-1">Shipping:</label>;
  <select name="select-choice-1" id="select-choice-1" data-theme="a">
    <option value="apple">apple</option>;
    <option value="banana">banana</option>;
    <option value="grapes">grape</option>;
    <option value="onion">onion</option>;
  </select>
</div>

```

## Location Selection

---

## Fixed Location

---

Fix the footer bar position to the top and bottom of the browser. If the scroll event takes place, the footer bar is always placed in the top and at the bottom of the browser. Add **data-position="fixed"** to Header bar's `<div data-role="footer">`. [fixed position sample](#)

```
<div data-role="footer" data-position="fixed">  
  <h1>header title</h1>  
</div>
```

---

## Full Screen Mode

---

You can fix the Header/footer bar to the top or at the bottom of the browser, or remove the bar. If the event takes place, the Header/footer bar appears or disappears. For details, refer to [header bar](#)'s full screen mode.