

Header bar

Header bar is generally located in the top of the browser for navigation between pages. Buttons or header titles can be placed in the left and right of the bar.

Base Code

Header bar is generally provided in black. The height of the header bar varies depending on the title size.

Header title

```
<div data-role="header">
  <h1>headertitle</h1>
</div>
```

Color Change

Add **data-theme='[applied theme: a~g]'** to the base code `<data-role="header">` tag.

data-theme="a"

data-theme="b"

data-theme="c"

data-theme="d"

data-theme="e"

data-theme="f"

data-theme="g"

```
<div data-role="header" data-theme="e">
  <h1>data-theme="e"</h1>
</div>
```

Add buttons

Adding the anchor link in the header bar will create a button automatically. Buttons are generated from the left and you cannot create more than two buttons. To align buttons, add the base type `<data-role="header">` **data-position="inline"**. For button shapes, refer to [ICon_](#).

[Cancel](#)

Add buttons in the header bar

[Save](#)

```
<div data-role="header" data-position="inline">
```

```
<a href="#" data-icon="delete">Cancel</a>
<h1>Add button in header bar</h1>
<a href="#" data-icon="check" data-theme="b">Save</a>
</div>
```

Button Location

To designate the location for the button in the header bar, add **class="ui-btn-[right, left]"** to the button.

class="ui-btn-right"

[Options](#)

```
<div data-role="header" data-position="inline" >
  <h1>class="ui-btn-right"</h1>
  <a href="index.html" data-icon="gear" class="ui-btn-right">Options</a>
</div>
```

Back

To create Back button in the Header bar, add **data-rel="back"**.

Back

```
back
<a href="#" data-icon="arrow-l" data-rel="back">back</a>
```

data-rel="back" may work different depending on the browser support elements. Hang a link to the previous screen and declare **data-direction="reverse"** to operate the link in addition to the screen transition effect.

Back

```
back
<a href="/guide/guide.do" data-icon="arrow-l" data-direction="reverse" >back</a>
```

Location Selection

Fixed Position

Fix the Header bar position to the top and bottom of the browser. If the scroll event takes place, the Header/footer bar is always placed in the top and at the bottom of the browser. Add **data-position="fixed"** to Header bar's `<div data-role="Header">`. [fixed position sample](#)

```
<div data-role="Header" data-position="fixed">
  <h1>header title</h1>
</div>
```

Full Screen Mode

You can fix the Header/footer bar to the top or at the bottom of the browser, or remove the bar. If the event takes place, the Header/footer bar appears or disappears. Add **data-fullscreen="true"** to `<div data-role="page">` tag. [fullscreen position sample](#)

```
<div data-role="page" data-fullscreen="true">
  <div data-role="header" data-position="fixed">
    <h1>header title</h1>
  </div>
  ...
  <div data-role="footer" data-position="fixed">
    <h1>Footer title</h1>
  </div>
</div>
```